

CE 0036 CPD 9165 001



Almeva AG

Industriestrasse 6,
CH-9220 Bischofszell

Bis und mit Ø160

| | | |
|------------------------------------|--|--------------------------|
| 0.1 Easy (einw.) | T120 - H1 - W2 - 020 - LI - E - U | <input type="checkbox"/> |
| 0.3 Double (LIK) | T120 - H1 - W2 - 000 - LI - E - U1 | <input type="checkbox"/> |
| 0.5 Double (LIB / LIL) | T120 - H1 - W2 - 000 - LI - E - U0 | <input type="checkbox"/> |
| 0.7 Double (LAB / LAL / LAM / LAC) | T120 - H1 - W2 - 000 - LE - E - U0 | <input type="checkbox"/> |
| 0.9 Schacht | T120 - H1 - W2 - 000 - LI - E - U0 | <input type="checkbox"/> |
| Temperatur-Stufe: | T120 | |
| Gasdichtheit: | H1 | |
| max. Höhe: | 30 m | |
| Windlastbeständigkeit: | 0.7: 3 m nach der letzten Befestigung 4 m zwischen zwei Befestigungen | |
| Wärmedurchlass-Widerstand | R00 | |
| Distanz zu brennbaren Stoffen: | 0.0 - 0.1: ≥ 20 mm 0.2 - 0.9: ≥ 00 mm | |



Einbaudatum:

Installateur: